



<p>Type</p> <p>Series 65/HHN REDUCED WALL DUCTILE HY X HY To AWWA C515</p>  <p>HYMAX GRIP® ends Class 150 NRS Ductile iron 250 PSI Size 2"-12"</p>	<table border="1"> <thead> <tr> <th data-bbox="609 163 738 184">AVK Ref. #</th> <th data-bbox="889 163 927 184">Size</th> <th colspan="2" data-bbox="1133 163 1198 205">Weight</th> <th data-bbox="1442 163 1490 205">Price</th> </tr> <tr> <td></td> <td></td> <th data-bbox="1101 184 1125 205">kg</th> <th data-bbox="1206 184 1230 205">lb</th> <th data-bbox="1442 184 1490 205">US \$</th> </tr> </thead> <tbody> <tr><td>65-050-HHN</td><td>2"</td><td>N/A</td><td>N/A</td><td>1,068</td></tr> <tr><td>65-065-HHN</td><td>2.5"</td><td>N/A</td><td>N/A</td><td>1,293</td></tr> <tr><td>65-080-HHN</td><td>3"</td><td>N/A</td><td>N/A</td><td>1,436</td></tr> <tr><td>65-100-HHN</td><td>4"</td><td>38</td><td>83</td><td>1,599</td></tr> <tr><td>65-150-HHN</td><td>6"</td><td>60</td><td>131</td><td>2,123</td></tr> <tr><td>65-200-HHN</td><td>8"</td><td>88</td><td>193</td><td>3,329</td></tr> <tr><td>65-250-HHN</td><td>10"</td><td>127</td><td>279</td><td>4,843</td></tr> <tr><td>65-300-HHN</td><td>12"</td><td>159</td><td>349</td><td>6,017</td></tr> </tbody> </table> <p>Add \$60 for anode machining</p>	AVK Ref. #	Size	Weight		Price			kg	lb	US \$	65-050-HHN	2"	N/A	N/A	1,068	65-065-HHN	2.5"	N/A	N/A	1,293	65-080-HHN	3"	N/A	N/A	1,436	65-100-HHN	4"	38	83	1,599	65-150-HHN	6"	60	131	2,123	65-200-HHN	8"	88	193	3,329	65-250-HHN	10"	127	279	4,843	65-300-HHN	12"	159	349	6,017
AVK Ref. #	Size	Weight		Price																																															
		kg	lb	US \$																																															
65-050-HHN	2"	N/A	N/A	1,068																																															
65-065-HHN	2.5"	N/A	N/A	1,293																																															
65-080-HHN	3"	N/A	N/A	1,436																																															
65-100-HHN	4"	38	83	1,599																																															
65-150-HHN	6"	60	131	2,123																																															
65-200-HHN	8"	88	193	3,329																																															
65-250-HHN	10"	127	279	4,843																																															
65-300-HHN	12"	159	349	6,017																																															
<p>Series 65/HFN REDUCED WALL DUCTILE HY X FL To AWWA C515</p>  <p>HYMAX GRIP® X Flanged end to ANSI B 16.1 Class 125 NRS Ductile iron 250 PSI Size 2"-12"</p>	<table border="1"> <tbody> <tr><td>65-050-HFN</td><td>2"</td><td>N/A</td><td>N/A</td><td>N/A</td></tr> <tr><td>65-065-HFN</td><td>2.5"</td><td>N/A</td><td>N/A</td><td>N/A</td></tr> <tr><td>65-080-HFN</td><td>3"</td><td>N/A</td><td>N/A</td><td>N/A</td></tr> <tr><td>65-100-HFN</td><td>4"</td><td>34</td><td>73</td><td>1,347</td></tr> <tr><td>65-150-HFN</td><td>6"</td><td>54</td><td>119</td><td>1,811</td></tr> <tr><td>65-200-HFN</td><td>8"</td><td>78</td><td>170</td><td>2,717</td></tr> <tr><td>65-250-HFN</td><td>10"</td><td>115</td><td>253</td><td>4,277</td></tr> <tr><td>65-300-HFN</td><td>12"</td><td>151</td><td>331</td><td>5,357</td></tr> </tbody> </table> <p>Add \$60 for anode machining</p>	65-050-HFN	2"	N/A	N/A	N/A	65-065-HFN	2.5"	N/A	N/A	N/A	65-080-HFN	3"	N/A	N/A	N/A	65-100-HFN	4"	34	73	1,347	65-150-HFN	6"	54	119	1,811	65-200-HFN	8"	78	170	2,717	65-250-HFN	10"	115	253	4,277	65-300-HFN	12"	151	331	5,357										
65-050-HFN	2"	N/A	N/A	N/A																																															
65-065-HFN	2.5"	N/A	N/A	N/A																																															
65-080-HFN	3"	N/A	N/A	N/A																																															
65-100-HFN	4"	34	73	1,347																																															
65-150-HFN	6"	54	119	1,811																																															
65-200-HFN	8"	78	170	2,717																																															
65-250-HFN	10"	115	253	4,277																																															
65-300-HFN	12"	151	331	5,357																																															